



BENTOGLISS 119 DISA

Release agent for DISAMATIC lines; solvent-free.

Product Properties

BENTOGLISS 119 DISA is a release agent, especially suited for DISAMATIC lines working with enclosed spraying units. BENTOGLISS 119 DISA does not contain any aromatics and thus has a neutral odor.

Application

To obtain an evenly thin coat and optimum release properties with maximum economic advantages, we suggest to apply BENTOGLISS 119 DISA by spraying.

Analytical values

- Alloy of mineral oils with additives
- Condition: liquid
- Color: clear
- Odor: characteristic
- Viscosity[40°C]: 3.5-4.5 cSt
- Density [15°C]: 0,815 – 0,830 g/cm³
- Flash point DIN 51755: > 70°C

Storage & Handling

- Product Storage Conditions: 12 months under normal conditions.
Storage and operating temperature: +10°C to + 40 °C
Transport temperature: - 10°C to + 40 °C

Packaging

- Drum (200 ltr) : 170 kg
- Container (1000 ltr) : 800 kg

Handling of BENTOGLISS 119 DISA

- Arrange for good ventilation.
- Do not inhale the fumes.
- Avoid skin and eye contact.
- Labelling: Please refer to the Safety Data Sheet



BENTOGLISS 119 DISA

Complimentary Products

Bentonite bonded green sand