



BENTOGLISS 121

Release agent for bentonite-bonded sand/green sand solvent-free

Product Properties

BENTOGLISS 121 is a release agent, especially suited for molding lines and manual molding units. BENTOGLISS 121 does not contain any solvents and thus is especially environmentally friendly and harmless to health. To obtain an evenly thin coat and optimum release properties with maximum economic advantages, we suggest to apply BENTOGLISS 121 with a spray gun.

Analytical values

- Alloy of mineral oils with additives
- Condition: liquid
- Color: yellow
- Odor: oil-like
- Viscosity[40°C]: 7.0-8.5 cSt
- Density [15°C]: 0,830-0,855 g/cm³
- Flash point DIN 51755: > 120°C

Storage & Handling

- Product Storage Conditions: 12 months under normal conditions.
- Storage and operating temperature: +10°C to + 40 °C
- Transport temperature: - 10°C to + 40 °C

Packaging

- Canister: 10 kg
- Steel keg: 20 kg
- Drum: 170 kg
- Container: 800 kg

Handling of BENTOGLISS 121

- Arrange for good ventilation
- Do not inhale the fumes
- Avoid skin and eye contact
- Labelling: Please refer to the Safety Data Sheet



BENTOGLISS 121

Complimentary Products

Bentonite bonded green sand

Bentogliss is a registered trademark of Clariant AG.