



Press release

Farewell chunky graphite thanks to SMW inserts™

Hilden, May 7, 2013 – The production of high-stress cast parts made from cast iron with nodular graphite is a particular challenge for foundries, as high demands, amongst other things, are made on the inoculation technique used and the inoculants. The use of pure charge materials in the burden is essential for successful cast part production. The pig iron used, the scrap steel or returns may not contain any disruptive impurities. The following are thus an important prerequisite for preventing graphite degeneration, such as chunky graphite: Check for harmful trace elements in the base materials, magnesium treatment agents and inoculants and coordinate with regard to the chemical compositions.

ASK Chemicals Metallurgy GmbH has, with the development of the SMW insert™, now succeeded in developing an inoculant that gives foundries a decisive procedural advantage in the production and development of better quality cast parts with thicker walls made from cast iron with nodular graphite.

The mold inoculant SMW insert™ excels, in this connection, due to a wide range of advantages. The mold inoculation with the cerium- and bismuth-based SMW insert™ prevents chunky graphite by neutralizing disruptive elements. A further advantage of the inoculation process is that it takes place without oxygen. Oxide and sulfide formations as well as oxidic impurities, such as slag, are thus minimized. The graphite degeneration is prevented due to the very late inoculation of the iron. This process ensures an optimal, uniform inoculation of the entire cast part during mold filling. The nodule count can be increased up to 400 nodules per mm² and the nodule size reduced. The mechanical properties, e.g. strength and toughness, are optimized depending on the wall thickness. Additional procedural advantages of the mold inoculant SMW insert™ are due to the ability to precisely calculate the required dose. The use of an additional metal stream inoculation device can thus be dispensed with.

Use of SMW inserts™

The SMW insert™ can be used depending on the trace element content. The recommended amount to be added is in the region of up to 0.2%. We recommend that it be used in combination with the already established mold inoculant Germalloy™ where the influence of trace elements is lower. Depending on the trace element content as well as for component-based reasons, the ratio can, for example, be 0.10% SMW insert™ and 0.10% Germalloy™ for an inoculant addition of 0.20%. All previously known P inserts, P 300 to P 30, are also available as SMW inserts™ (Figure 1).

The SMW insert™ can be used in combination with a preconditioning agent, e.g. VL (Ce) 2 and with a cerium-free and/or low-content-cerium FeSiMg master alloy, e.g. VL 63 O or VL 63 M 3. Small mold inoculation bodies should, in all cases, be installed in the pouring basin as "starters" – e.g. P 300, P 500 and/or P 800 – in order to ensure efficient and prompt inoculation. It is thus ensured that the cast iron that flows in first – which can solidify near the risers – does not have any chunky graphite and the inoculation effect is realized right from the start of the mold filling.

In addition to the quality aspects, there are also economic reasons for using these mold inoculants according to Dr. Sven Uebrick, Global Product Manager ASK Chemicals Metallurgy. These effects have been investigated in detail in extensive tests by ASK Chemicals Metallurgy GmbH and verified in practice.

Images for the press release



Figure 1: SMW inserts™ in different sizes, P 300 to P 30, ASK Chemicals Metallurgy GmbH



About ASK Chemicals

ASK Chemicals is one of the world's largest suppliers of foundry chemicals, with a comprehensive product and service portfolio of binders, coatings, feeders, filters and release agents, as well as metallurgical products including inoculants, Mg-treatment and inoculation wires and master alloys for iron casting.

ASK Chemicals is represented in 25 countries with 30 sites, 20 of which operate their own production, and employs approx. 1,800 people worldwide. With research and development in Europe, America and Asia, ASK Chemicals sees itself as the driving force behind industry-specific innovations and is committed to offering customers a consistently high level of quality. Flexibility, quickness, quality and sustainability as well as cost-effective products and services are of key importance.

Press contacts

Company contact

Corporate Communications
ASK Chemicals GmbH
Verena Skelnik
Manager Marketing & Communications
Reisholzstraße 16-18
40721 Hilden

Tel. +49 211-71103-0
Fax +49 211-71103-70

www.ask-chemicals.com
info@ask-chemicals.com

Press agency

ProTEC Marketing
Andrea B. Ferkinghoff
Managing Director
Würzburger Str. 23
97230 Estenfeld/Würzburg
Germany

Tel. +49 9305-98885-21
Fax +49 9305-98885-19

www.protec-marketing.de
Ferkinghoff@protec-marketing.de