



ZIP SLIP 185 V

Aluminum-pigmented liquid parting

Performance

Fast-drying aluminum-pigmented liquid parting supplied ready to use that contains significantly less VOCs than standard solvent based releases.

- Fast-drying
- Ready for use
- Lower VOCs

Features	Benefits
Multiple uses	Will release from all substrates (metal, wood, plastics)
Excellent release	Less scrap, better core and pattern definition
Multiple releases	Cost savings
Better aluminum suspension	Less mixing required

Application

The solids in ZIP-SLIP 185V parting will settle out of suspension during transportation or storage but are easily re-suspended with a small amount of agitation before use. As the solvent system evaporates fast, the ZIP-SLIP 185V parting may increase in viscosity and become difficult to apply. Steps should be taken to minimize evaporation. ZIP-SLIP 185V parting contains solvent which may be harmful to rubber and/or urethanes.

ASK Chemicals has several PEPSET Phenolic urethane and CHEM-REZ furan no-bake binder systems designed to meet various productivity, environmental, and casting quality needs.



ZIP SLIP 185 V

Product Storage condition

- 2 years minimum under normal conditions in sealed original container.
- As with all release agents, a first-in, first-out stock rotation is recommended.
- Store in well-ventilated, dry area at temperatures of 40°F to 80°F.

Packaging

851362	Minitanks	330 gallons	2580 lbs. net
851364	Drums	55 gallons	430 lbs. net
851365	Pails	5 gallons	35 lbs. net
851363	Pails	1 gallon	6.9 lbs. net

Handling of

ASK Chemicals maintains material safety data sheets on all of its products. Material safety data sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Our material safety data sheets should be read and understood by your personnel before using ASK chemicals' products in your facilities.

Typical Features (1)

Color*: Silver

Density: Approx 8.6 lbs/gal

* Slight differences in color are caused by minor variations of the natural raw materials or changes in color during tempering of the refractory solids, and have no influence on the product quality.

(1) Typical property values only, not to be construed as specifications. Actual properties will be dependent on the history of the material.