



ZIP SLIP LP 78 1495

Aluminum-pigmented liquid parting

Performance

Fast-drying aluminum-pigmented liquid parting supplied ready to use.

Features	Benefits
Multiple uses	Will release from all substrates (metal, wood, plastics)
Excellent release	Less scrap, better core and pattern definition
Multiple releases	Cost savings
Better aluminum suspension	Less mixing required

Application

The solids in ZIP-SLIP LP78 1495 parting will settle out of suspension during transportation or storage but are easily re-suspended with a small amount of agitation before use. As the solvent system evaporates fast, the ZIP-SLIP LP78 1495 parting may increase in viscosity and become difficult to apply. Steps should be taken to minimize evaporation. ZIP-SLIP LP78 1495 parting contains solvent which may be harmful to rubber and/or urethanes.

Product Storage condition

- 2 years minimum under normal conditions in sealed original container.
- As with all release agents, a first-in, first-out stock rotation is recommended.
- Store in well-ventilated, dry area at temperatures of 40°F to 80°F.

Packaging

603876	Minitanks	330 gallons	1860 lbs. net
135529	Drums	55 gallons	310 lbs. net
32741	Pails	5 gallons	26 lbs. net
604162	Pails	1 gallon	5 lbs. net

ASK Chemicals L.P. | 495 Metro Place South Suite 250 | Dublin, Ohio 43017 | Tel. +1 800-848-7482 | info.usa@ask-chemicals.com | www.ask-chemicals.com

The following marks are registered by ASK Chemicals GmbH, ASK Chemicals Metallurgy GmbH or ASK Chemicals LP in one or more countries: ALPHASET, ASKOBOND, ASKRONING, ASKURAN, BERANOL, BETASET, CERAMCOTE, CHEM-REZ, DENODUL, DISPERSIT, EXACTCAST, EXACTCALC, EXACTFLO, ECOCURE, ECOPART, GERMALLOY, INFORM, INOBAKE, INOSOLVE, INOTEC, ISOCURE, ISO-FAST, ISOMAX, ISOSEAL, ISOVENTS, LINO-CURE, MAGNASET, MIRATEC, NOVACURE, NOVANOL, NOVASET, OPTIGRAN, OPTINOC, PEP SET, REMMOS, SMW-INSERT, SOLITEC, STA-HOT, UDICELL, VEINO, VEINO ULTRA, VELVACOAT, ZIP SLIP, ZIP CLEAN.



ZIP SLIP LP 78 1495

Handling of

ASK Chemicals maintains material safety data sheets on all of its products. Material safety data sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Our material safety data sheets should be read and understood by your personnel before using ASK chemicals' products in your facilities.

Typical Features (1)

Color*: Silver

Density: Approx 6.18 lbs/gal

* Slight differences in color are caused by minor variations of the natural raw materials or changes in color during tempering of the refractory solids, and have no influence on the product quality.

(1) Typical property values only, not to be construed as specifications. Actual properties will be dependent on the history of the material.